

Advantages of the PG2 scanning gonio-photometer

Key feature of the principle of a *scanning* gonio-photometer


- detector system is mechanically moved to position around sample
- clear separation of angular position and signal processing
- detector response identical at all positions
- detector can be verified externally
- multiple parallel detectors are possible
- detectors are adaptable to task (spectral range, solid angle)
- no intermediate components in beam path that add to scattering and cross-talk, leads to lower errors and detailed understanding of residual error sources
- instrument signature is well defined and might be adaptable to task

Specific key feature of the pab PG2

- full 3D: allows to set two incident angles, two outgoing angles
 - allows measurement of transmittance and reflection
 - scan-area was maximised, covers nearly the full sphere around sample
 - minimised self-shading by arm in reflection measurements
 - the size of 1m between sample and detector achieves small solid angle offering high resolution
 - modular design, adaptable to client's tasks
 - precision in angular positioning, achieved by high-end drive systems
 - intrinsic cross-checking of angular position by using both arm configs for one outgoing direction
 - uses beam as reference requires no reflective standard as reference
 - speed of positioning
 - in-house developed fast sensor technology
 - fast measurements on-the-fly, while detector is moving
 - detectors for UV, VIS and IR available
 - extension with Zeiss spectral detectors, 330nm to 1.7um
 - optional extra light-sources installable by end-user
 - as selection of sample mounts match user's task and projects
 - control program and data-storage interface easily to user's site requirements
 - direct contact with PG2 development
 - 25 years of experience in BSDF measurement, 10+ years of international PG2 support
- some details of installed PG2 are given on the following pages


- Heavy-duty armB
- 4-channel standard sensors
- Spectrometer option
- *phirot* sample mount
- Ceiling rail for crane to lift *phirot* sample mount

RealisticGraphicsLab (RGL),
EPFL, Lausanne



- 4-channel standard sensors
- Spectrometer option (lower sensor in image)
- Multiple cameras and lenses, selected by client
- Each camera is mounted on a sled, user exchangeable

RGL, EPFL



- Client supplied camera control sub-system at armB
- Component rotates together with detector-head
- Mechanical adapter and power supply with sliprings by pab Ltd

RGL, EPFL




- *phirot2* mounted on PG2
- overhead crane for *phirot* mounting
- ceiling light used during mounting of sample and maintenance
- all PG2 installations use high-power outdoor LED light fittings to achieve sufficient light levels during maintenance despite the black walls and ceiling

RGL, EPFL




- Merge of classical PG2 light system and client supplied extra set-up
- Specifications of carrier systems by pab Ltd
- Control of components through USB at PG2-control-PC running Linux

RGL, EPFL




- Measuring refraction of a prism
- PG2 Manual sample mount combined with a standard mount for optical components

pab Ltd



- *LargeSampleMount* with glazing sample during set-up of PG2
- Dual light sources: Halogen and Xenon
- 4-channel std sensors
- Shown here before installation of black curtains

Solar Energy Research Institute of Singapore (SERIS)



- Manual sample mount during setup of PG2
- Xenon light source in foreground
- 4-channel std sensors

HSLU, Lucerne




- special Si sensor with smaller shadow region around sensor
- used for measuring reflection BSDF very close to the retro-reflected peak
- custom developed for consulting project with retro-reflectors used in industrial light-curtains

pab Ltd




- BRDF visualisation using the program *mountain*
- Plot shows reflective part of BSDF for incident angle 10deg
- A "classical BSDF" of a rough Aluminium sample: material scatters around the ideal reflected peak
- Plot uses linear Z-scale

pab Ltd




- Detail of above dataset, showing individual data points with 0.3deg spacing
- Each dataset contains two configurations of the PG2 for the same position of the the detector head: one is shown with pink-colored datapoints, the other one with yellow-colored datapoints. Their matching values intrinsically cross-check positional accuracy,

pab Ltd




- Transmission DSF visualisation of a light-redirecting material, used for daylighting indoor spaces
- Peak on left side of centre is directly transmitted light
Peaks on right side are light redirected.
In an installed glazing this would be redirected towards the ceiling
- Peaks and 'ridge' use an adaptive refinement with closely spaced measurement points
- Plot uses a logarithmic Z-scale

pab Ltd



- Transmission DSF visualisation of a light-scattering material, used for daylighting indoor spaces
- surface is regularly embossed with small geometric pyramids
- normal incident direction
- Note that peaks are not artifacts, since each peak is resolved by the scan pattern
- The region of interest uses an adaptive refinement with closely spaced measurement points
- Plot uses a logarithmic Z-scale




pab Ltd

- Spectral BRDF for glossy yellow paint
- incident direction 30deg, plot is centred around ideal reflected peak
- spectrum shown for one outgoing angle
- interactive display, using program *mountain*
- Angular plot uses a log Z-scale spectral plot uses linear scales

```

s8_array"
.172] min=1.28e-02 max=5.96e+01 int=9.05e-02 front,ref1 log deca 8
.3 mrad phi_step= 10deg
-gloss" sample_name="yellow glossy paint"
    
```



pab Ltd

- Two PG2 during assembly at a local steel building company

pab advanced technologies Ltd
 reg in England&Wales #5794152
 Peter Apian-Bennewitz
 79114 Freiburg, Germany
 Tel +49-761-4766302
 web-site: <http://www.pab.eu>
 example data: <http://bme.pab.eu>



All data was compiled with care, but we reserve the right to update specifications.

Images © pab Ltd, published with permission by the clients
 pab® is a registered trademark

\$\$d: PG2-advantages.sla,v 1.12 2020/01/18 12:14:44 apian Exp \$